

15" POS ALL-IN-ONE TERMINAL

Powerful . Quality . Ultra Slim

Features:

LONGSHINE's model 15S-BT was designed for applications which require high performance and installation feasibilities. Through it's high degree of adjustable operation angles, it adapts to maximal installation environments. Your total cost of ownership will also be significantly reduced through competitive hardware costs, improved efficiencies and minimal administration efforts. Finally, high product quality ensures a long lifecycle.

Maximise the usage, minimize the cost

Platforms Quad Core covers all needs

- Flexibility of power

Touch type

- 15" Projected Capacitive Touch

Zero bezel design

- Water and dust proof sealing for wide range of usage

New feasible compact design

- Easily configured on the counter to suit the needs and demands of the user

Fanfree design

- Contributes to a pleasant quiet working environment

Performance

Fits into any POS software environment with relative ease

- 15S-BT provides a wide range of platforms to cover all software needs



Enhanced by  Bay Trail and Haswell platforms




RoHS
Compliant

CE FC



Hardware Specification	
CPU	Intel® Celeron® Processor J1900 (Clockspeed: 2.0 GHz, Turbo Speed: 2.4 GHz, Cores: 4)
System Memory	2GB Standard, Maximum 8G (DDR3L SO-DIMM socket x 2)
Graphics	Intel® Gen7 Intel® Graphics DX 11, OGL3.2
Audio	Realtek ALC662 HD Audio
Display	15" TFT-LCD /1024 X 768 (LED backlight)
	Touch Screen:15" Projected Capacitive touch
Storage	1x 2.5" SATA II HDD/SSD
Color	Black or White
External I/O Ports	
USB	6 (2 x USB 3.0 , 4 x USB 2.0) ,
COM port	3 x RJ45 with 5V/12V power selectable
LAN	1 x 10/100/1000Mbps
DC input	1 x 12V
VGA	1
Audio I/O	2 (Mic-in , Line out)
Cash drawer	1 x RJ-11 (12V/24V)
Optional Peripherals	
MSR	3 Tracks , JIS-I or II
2-in-1 Reader	MSR+ RFID or MSR+iButton
Customer Display	2 x 20 VFD stand-alone type
2nd Display	7"/10"/15" monitor
Speaker	2 x 3W
OS Support	
Windows	Windows Embedded POSReady 7 (64bit) , Windows Embedded Industry 8.1 (64bit) , Win10 IoT Enterprise for Retail (64bit)
Linux	Per Request
Environment	
Operating Temperature	0°C ~ 35°C (32°F ~ 94°F)
Storage Temperature	-10°C ~ 55°C (14°F ~131°F)
Relative Humidity	10% ~ 90% (Non-Condensing)
Sealing	IP54 (display side)

Features and specifications are subject to change without prior notice.

CONTACT

LONGSHINE Technologie GmbH

Headquarters:

An der Strusbek 9, 22926 Ahrensburg, Germany

No 945 Boai Street, Jubei City, Hsinchu, Taiwan 30265

TEL: +49 4102 49220 FAX: +49 4102 40109

www.longshine.de

All rights reserved, including intellectual property rights. Changes to technical data reserved.

Delivery subject to availability. All liability that the data and illustrations are complete, actual or correct is excluded. Copyright © 1981-2017 LONGSHINE Technologie GmbH.